

Speed of tangential feed: $v_{f,t} = n_w \cdot f_t = 955 \cdot 0.14 = 133.7 \text{ mm/min}$.
 Feed along the axle: $f_a = f_t / \tan \varphi = 0.14 / \tan 30^\circ = 0.242 \text{ mm/workpiece rev.}$
 Speed of feed along the axle: $v_{f,a} = n_w \cdot f_a = 955 \cdot 0.242 = 231.6 \text{ mm/min}$.
 Rotary speed of tool: $n_s = \frac{v_{f,t}}{d_s \cdot \pi} = \frac{133.7}{200 \cdot \pi} = 0.212 \text{ 1/min}$
 Angular velocity of the tool: $\omega_s = \frac{n_s}{9.55} = \frac{0.212}{9.55} = 0.023 \text{ rad/min}$
 Main time of machining: $t_g = \frac{L_w}{v_{f,a}} = \frac{20}{231.6} = 0.086 \text{ minute} \rightarrow 5.2 \text{ secundum}$.

SUMMARY

The technique of surface creation of rotation turning is different from hard turning procedures applied so far. In the new procedure the generatrix of the cylindrical surface is a straight line theoretically as well which is free from feed traces usual in turning or furrows from feed. Thus, on the generated surface there are no periodical topography patterns. The turned surface is suitable for sealing and changing for the more expensive grinding is not necessary. Beyond that the advantage of dry machining is kept and because of the relatively longer feed along the axle its productivity is significantly higher than that of the traditional hard turning.

ACKNOWLEDGEMENT

This paper was prepared by the support of the Hungarian Scientific Research Found, which the authors highly appreciate. The number of assignment is: OTKA K-78482.

The described work was carried out as part of the TÁMOP-4.2.1.B-10/2/KONV-2010-0001 project.

REFERENCES: 1. Karpushewski – Knocke – Hipke: Gear Finishing by Abrasive Processes, *CIRP Annals* 57 (2008); pp.621-640; 2. Weisser JG: Patent von Werkzeugmaschinenfabrik, *St. Georgen, Swarzwald, Deutschland*, 2004. 3. Kummer N, Voght B.: Drallfreies Drehen ersetzt Schleifprozesse; *IDR* 4/2004, pp.2-5; 4. Szabó S.: A rotációs előtolással történő esztergálás vizsgálata, *Oktatási segédlet* (kézirat), ME-GTT, 2009.; 5. Klingauf W: Drehen ohne drall, *Fertigung Jan/Febr. 2005.* pp.16-18.; 6. <http://www.weisser-web.com/index.php?id=21&L=0>; [7] http://www.mas-tools.de/fm/_16/Rotationsdrehen.1020.pdf

Поступила в редколлегию 16.04.2011

UDK 621.9

J. Kundrak, Prof Dr. Habil., L. Raczkovi, Miskolc, Hungary

INVESTIGATION ON WEAR AND TOOL LIFE OF CUTTING TOOLS

Я. КУНДРАК, Л. РАЦКОВИ

ДОСЛІДЖЕННЯ ЗНОСОСТІЙКОСТІ РІЗАЛЬНИХ ІНСТРУМЕНТІВ

Зношування різального інструменту визначає відвід стружки й стійкість інструменту з погляду економічної ефективності різання. Причина в тому, що надтверді інструменти коштують дорого, а оброблені деталі повинні мати строгі параметри відносно точності і якості. Саме тому дослідження цих інструментів має велике значення. Стаття присвячена деяким особливостям кубічного нітриду бора та інструментів, що впливають на визначення терміну служби інструмента.

Ключові слова: зношування інструмента, термін служби інструмента, інтенсивність зношування

Износ режущего инструмента определяет отвод стружки и стойкость инструмента с точки зрения экономической эффективности резания. Причина в том, что сверхтвердые инструменты стоят дорого, а обработанные детали должны иметь строгие параметры в отношении точности и качества. Именно поэтому исследование этих инструментов имеет большое значение. Статья посвящена некоторым особенностям кубического нитрида бора и инструментов, влияющим на определение срока службы инструмента. Ключевые слова: износ инструмента, срок службы инструмента, интенсивность износа

The wear of cutting tools is determinant in chip removal and tool life is in economic efficiency of cutting. The reason is that superhard tools are expensive and surfaces or parts machined by them have to fulfill strict requirements referring to the accuracy and quality. That is why investigation on these tools have a major importance. The paper focuses on some wear feature of CBN tools and on determining of tool life.

Keywords: tool wear, tool life, wear intensity

INTRODUCTION

Hard machining is characteristic of the machining of hardened parts with 50-65 HRC hardness. Owing to superhard tool materials in finish machining hard turning more and more comes into view against grinding. The advantages of hard turning are the higher production flexibility, the higher material removal rate, the higher productivity and through all these, the reduction of costs of manufacturing [1, 2]. Despite the machining that uses no CL at all, the produced part has got good surface integrity and roughness appropriate for precision machining. These advantages however return just in case these tool materials ensure the appropriate shape and dimensional accuracy besides optimal tool life. Therefore several researchers deal with the examination of the wear mechanism of CBN tools. The typical CBN tool wear mechanisms are decisively abrasion as well as adhesion and diffusion wear [3]. Several mathematical models have been created to describe these wear mechanisms [4, 5]. The main wear patterns that can be observed on CBN tools are: decisively flank wear as well as crater wear, edge wear, nose wear, chipping, thermal shock cracks [3]. The observed wear patterns are caused by not only one wear process, but the simultaneous appearance of the above mentioned wear processes.

Flank wear is the most reported wear pattern because it is the determinant wear pattern due to the hardness of workpiece, crystal structure, and the particularity of chip removal, and it is used as a tool life criterion. Since the CBN tools are brittle, microchipping and/or tool breakage are typical, which are caused by the increasingly positive rake angle before tool flank wear reaches the pre-specified flank wear criterion. To better predict the tool life, it is recommended to use the crater-wear depth in addition to the flank-wear width as the tool life criteria [3]. It is necessary to take difference between low content CBN tools (CBN-L) and high content CBN tools (CBN-H) in case of wear examination, and between continuous and interrupted cutting in case of determination of wear rate. Tool materials content 50-75 vol.% CBN grains with ceramic binder are noted as CBN-L and tool materials content ~90 vol.% CBN grains with metallic binder are noted as CBN-H [6]. When researchers tested CBN tool wear several surprising phenomena were observed: CBN-L tool materials gave longer tool life, the rate of wear was smaller and the surface quality was better than CBN-H [7]. This is surprising because CBN-H has greater hardness and fracture toughness than CBN-L. There are many different explanations for these puzzling phenomena. Some researchers suggest the longer tool life of CBN-L is due to greater bonding strength, some propose that the welded layers on the tool flank wear land of CBN-L create a protection effect, and others attribute the lower thermal conductivity of CBN-L to the softening of workpieces in the shear zone [7]. Chou et al. have done experiments comparing flank wear land between BZN6000 (CBN-H) and BZN8100 (CBN-L) tool materials in case of machining hardened steels [7]. Chou et al. based on scanning electron micrographs explained that the greater wear resistance of low BN content tools is caused by a transferred layer on the flank wear land. For low BN content tool the transferred layer is smooth and uniform, while the transferred layer on high content BN tools is rough, striated. This is caused by hard wear debris during abrasion and plucked out CBN particles from the tool itself [7]. Many hard machining operations involve interrupted cutting conditions such as gear facing, and spline shaft turning. In these cases the interrupted path of cutting and the high density of load changes make the tool wear more intense [8]. Despite the increased applications, few researchers dealt with the examination of the process. The initial researches focused on brittle fracture and sudden tool failure. Today the tool entry and exit angles, cut and non cut time ratio, thermal cracking, thermal shock cracking and cutting edge effect are examined [8]. Naikai et al. [9] tested various low CBN content tools in interrupted turning of hardened steels and concluded that CBN tools with smaller grain sizes have better wear resistance in interrupted hard turning. This trend is a result of increased hardness and transverse rupture strength by finer CBN grains. Dewes és Aspinwall [10] tested various CBN tools in milling hardened steels. It was reported that CBN-H performed better than CBN-L at high speed range, while at lower speed CBN-L had longer tool life. In addition, it was observed that chipping was a dominant wear mode.

1. EXPERIMENTS TO DETERMINE THE EXTENT OF WEAR

In recent years a lot of new information on hard turning enriched the technical literature [1, 2]. However, to make this advanced finish machining widespread,

further examinations are needed. So, besides the wear mechanisms and their forms of appearance, one of them is the study of the wear intensity of cutting tools to describe the tool life as accurately as possible. Determining the tool life is important for economic analysis and the planning of the technological process of parts alike. We did cutting experiments for hard machining, specifically boring. We chose internal cylindrical surfaces because machining of bores is almost as frequent as that of external surfaces and the tool wear is characterized by more intensive processes than in machining external surfaces. When producing these surfaces, because of their more difficult machining, earlier it was accepted to make concessions for accuracy, surface quality and economic requirements (and/or expectations) as regards to external cylindrical surfaces. These differences are narrowing because of the quality expectations of the product and the economy of production. The other aspect was that in machining holes the chip removal is characterized by more intense processes than in external surface machining. The effect of bore diameter was analysed because due to the geometrical and kinematic relations of chip removal, besides the cutting parameters, the bore diameter also affects the chip removal process [11]. During the experiments we machined internal cylindrical surfaces with different bore diameters with high CBN content tools and determined the relations with which the wear can be characterized.

2. CUTTING EXPERIMENTS

We did the experiments with two CBN tools having different quality and the same tool edge geometry (CBN 1 and CBN 2, the CBN 2 tool's grain size is smaller than 1 μm), with constant feed rate and depth of cut value, with different cutting speeds, while the bore diameter changes were studied. The cutting conditions were as follows:

- cutting tools: CBN 1 and CBN 2,
- tool edge geometry: $\gamma = -5^\circ$; $\alpha = \alpha' = 15^\circ$; $\lambda_s = 0^\circ$; $\kappa_r = 45^\circ$; $\kappa'_{r1} = 2^\circ$; $\kappa'_{r2} = 15^\circ$; $b_e = 0.3\text{mm}$,
- workpiece: hardened bearing steel: 100Cr6 HRC 62 $\pm$ 2,
- the examined range of the diameter of workpiece: $d = 45\text{--}100\text{ mm}$,
- machine tool: E400-1000 universal turning lathe,
- cutting parameters: $f = 0.075\text{ mm/rev}$; depth of cut : $a_p = 0.1\text{mm}$,
- cutting speed: $v_c = 11\text{--}120\text{ m/min}$,
- wear criterion: $VB = 0.4\text{ mm}$.

CBN tools wear primarily on the flank surface, and the extent of this wear determines the tool life. The 0.4 mm of dimension of this wear was chosen as tool life criterion. The CBN cutting tools until such value of wear can retain their good cutting ability, the increase of cutting force is insignificant, the roughness of the machined surface is not appreciably worse [11, 12].

During the experiments, we found that the protect layer and metal buildup which appear on the rake face of the tool have a significant impact on the working ability of the tool and they are a phenomenon determining the cutting process basically [12].

3 EVALUATION OF RESULTS

3.1 DETERMINATION OF WEAR INTENSITY

Based on the results of the experiments the wear intensity of tools was determined. The wear intensity was determined at different cutting speeds from the cutting length values which belonged to a 0.4 mm value of flank wear.

If the wear is counted for a unit of the cutting length one gets the wear intensity (k) [13]. According to this:

$$k = \frac{VB}{L} \quad (1)$$

where:

- k= wear intensity, $\mu\text{m}/10^3 \text{ m}$
- VB= flank wear, mm
- L=cutting length, m

The cutting length was determined using

$$L = \frac{C_{T1}}{v_c^2 + C_{T2} \cdot v_c + C_{T3}} \quad (2)$$

relation [14, 15].

The constants were determined by [12].

3.2 CALCULATED RESULTS

The wear intensity and the calculated constants of relation (1) are summarized in Tables 1-3. Figure 1 shows the cutting length. In function of cutting speed, the exact description of cutting length can be determined by equation (2). Figure 2 shows the changing of wear intensity in function of cutting speed.

Table 1 – Wear intensity (CBN 1 tool)

d mm	f mm/rev	a _p mm	v _c , m/min								
			11	20	29	40	50	68	92	105	120
			k $\mu\text{m}/10^3 \text{ m}$								
45	0.075	0.1	146	101	66	48	51	89	242	365	481
75			121	90	64	44	38	52	125	186	283
100			110	85	62	43	33	37	84	130	185

Table 2 – Wear intensity (CBN 2 tool)

d mm	f mm/rev	a _p mm	v _c , m/min								
			11	20	29	40	50	68	92	105	120
			k $\mu\text{m}/10^3 \text{ m}$								
45	0.075	0.1	302	168	87	63	109	366	1034	1561	2310
75			222	129	72	43	61	183	542	831	1242
100			175	111	66	38	43	123	366	537	846

Table 3 – The constants of tool life equation

d mm	f mm/rev	a _p mm	CBN 1			CBN 2		
			C _{T1}	C _{T2}	C _{T3}	C _{T1}	C _{T2}	C _{T3}
45	0.075	0.1	4.42·10 ⁶	-88.3	2463	1.26·10 ⁶	-76.0	1635
75			7.67·10 ⁶	-103.2	3382	2.08·10 ⁶	-82.2	1923
100			10.37·10 ⁶	-113.0	4019	2.97·10 ⁶	-86.6	2148




Figure 1 – The cutting length at different workpiece diameters +: d=45 mm; o: d=75 mm; x: d=100 mm (f=0.075 mm/rev.; a_p=0.1 mm; VB=0.4 mm)




Figure 2 – Changing of wear intensity in function of cutting speed at different bore diameters +: d=45 mm; o: d=75 mm; x: d=100 mm (f=0.075 mm/rev.; a_p=0.1 mm; VB=0.4 mm)

It can be established from the representation of wear intensity that with the increase of the value of cutting speed, the wear intensity decreases first, reaches a minimum value and then starts to increase. Beside relatively great feed rate in case of CBN 2 tool the wear intensity is smaller in a narrow range. It concerns both the ranges of cutting speed and the ranges of workpiece diameter. Increasing the diameter from 45 mm to 100 mm in case of tools CBN 1 and CBN 2, the maximum value of the cutting length increases by 30 %. Analysing Figure 1 and Figure 2 we can state that in case of different workpiece diameters the character of curves does

not change in function of cutting speed. Because of the greater chip deformation and thermal stress, with the decrease of the workpiece diameter, the wear intensity increases and the maximal cutting length together with its cutting speed decrease. The hard turning experiments applied for finish bore machining verify that the CBN cutting tools are characterized by long tool life. Performing the wear and tool life experiments in the usual way, with the suggested and in practice easily applicable relations the tool life path and the values of wear fluctuation can be determined.

4 CONCLUSIONS

The experiments were done with CBN tools (CBN1 and CBN2) with the same tool edge geometry and constant feed rate and depth of cut while we studied the effect of bore diameter at different cutting speeds. Because of the greater chip deformation and thermal stress, with the decrease of the workpiece diameter the intensity of wear increases while the maximal cutting length and its cutting speed are decrease.

When choosing the technological data attention must be paid that the optimal parameters can be reached in a relatively narrow range of cutting speed, and the recommended cutting speed values significantly depend on the values of feed rate, depth of cut as well as the machined workpiece diameter. With the correct choice of cutting parameters the economy of chip removal can be increased significantly.

Acknowledgement

The described work was carried out as part of the TÁMOP-4.2.1.B-10/2/KONV-2010-0001 project.

REFERENCES: 1. Tönshoff, H. K.; Arendt, C.; Ben Amor, R.: Cutting of hardened steel, Annals of the CIRP, Vol.49/2/2000 pp. 547-566. 2. Klocke F. Brinksmeier E., Weinert K.: Capability Profile of Hard Cutting and Grinding Processes, Annals of the CIRP Vol. 54/2 (2005) pp. 557-580. 3. Y. Huang, Y. K. Chou, S.Y. Liang: CBN tool wear in hard turning: a survey on research progresses. Int J Adv Manuf Technol (2007) 35:443-453 DOI 10.1007/s00170-006-0737-6. 4. Y. Huang, S.Y. Liang: Modelling of CBN tool crater wear in finish hard turning. Int. Adv Manuf Technol (2004) 24: 632-639. 5. Y. Huang, S.Y. Liang: Modeling of CBN Tool Flank Wear Progression in Finish Hard Turning. Transactions of the ASME Vol. 126, February 2004 p 98-106. 6. Davies, M.A., Chou, Y., Evans, C.J.: On Chip Morphology, Tool Wear and Cutting Mechanics in Finish Hard Turning. Annals of the CIRP Vol. 45/1/1996 pp.77-82. 7. Y. K. Chou, C.J. Evans, M.M. Barash: Experimental investigation on CBN turning of hardened AISI 52100 steel. J. of Mat. Proc. Technology 124 (2002) pp.274-283. 8. Y. Kevin Chou, Chris J. Evans: Cubic boron nitride tool wear in interrupted hard turning. Wear 225-229 1999, pp 234-245. 9. T. Naik, S. Nakatani, K. Tomita, M. Goto: Hard turning by PCBN, Conference of Superabrasive, Chichago, IL, June 12-14, 1991, pp.61-75. 10. R. C. Dewes, D. K. Aspinwall: The use of high speed machining for the manufacture of hardened steel dies, Transactions of NAMRI/SME 24 (1996) 21-26. 11. Kunderák J.: Validity of tool life equation when cutting with CBN tools. Proc. on the microCAD'97 International Computer Science Conference, Miskolc, Hungary, pp.97-100, 1997. 12. Kunderák J.: Results of research on the field of cutting with CBN tools. Proc. on the 2nd International Conference on Development of Metal Cutting, Košice, Slovakia, 1998, pp.H6-H11. 13. Horváth M.: Alkatrészgyártási folyamatok automatizált tervezése. / MTA SZTAKI tanulmányok 169/1985. Budapest, 205.p. 14. Mamalis AG, Kunderák J, Horváth M.: On a novel tool life relation for precision cutting tools, JOURNAL OF MANUFACTURING SCIENCE AND ENGINEERING - TRANSACTIONS OF THE ASME 127 (2): 328-332 may 2005. 15. Mamalis AG, Kunderák J, Horváth M.: Wear and tool life of CBN cutting tools, INTERNATIONAL JOURNAL OF ADVANCED MANUFACTURING TECHNOLOGY 20 (7): 475-479 2002.

Поступила в редколлегию 14.04.2011

УДК 621.923

В.И. Лавриненко, д-р техн. наук, Киев, Украина
В.Ю. Солод, канд. техн. наук, Днепропетровск, Украина,
Ю.И. Никитин, канд. техн. наук, И.В. Лещук, канд. техн. наук,
Б.В. Сытник, В.Г. Полторацкий, А.А. Девицкий, В.А. Скрыбин, Киев, Украина

ОСОБЕННОСТИ ШЕРОХОВАТОСТИ ОБРАБОТАННОЙ ПОВЕРХНОСТИ ПРИ ШЛИФОВАНИИ КРУГАМИ ИЗ СТМ С ОПОРНЫМИ ЭЛЕМЕНТАМИ В РАБОЧЕМ СЛОЕ

Досліджений вплив природи та розмірів опорних елементів з компактів КМ і мінеральних зернистих концентратів у робочому шарі круга на формування параметрів шорсткості і профілю мікронерівностей оброблюваної поверхні стосовно процесів шліфування сталі Р6М5 і твердого сплаву Т15К6.

Исследовано влияние природы и размеров опорных элементов из компактов КМ и минеральных зернистых концентратов в рабочем слое круга на формирование параметров шероховатости и профиля микронеровностей обрабатываемой поверхности применительно к процессам шлифования стали Р6М5 и твердого сплава Т15К6.

V.I. LAVRINENKO, V.JU.SOLOD, JU.I. NIKITIN, I.V. LEWUK, B.V. SYTNIK, V.G. POLTORACKIJ, A.A. DEVICKIJ, V.A. SKRJABIN
FEATURES OF THE PROCESSED SURFACE ROUGHNESS AT GRINDING BY CIRCLES FROM ULTRA-HARD MATERIAL WITH BASIC ELEMENTS IN THE WORKING LAYER

The paper focuses on the influence of nature and sizes of support units made of compacts KM and mineral grainy concentrates in the working layer of a circle upon the parameters of roughness as well as profile of microroughness of the treated surface in respect to the processes of grinding steel P6M5 and hard alloy T15K6.

Ранее [1, 2] нами были показаны особенности применения кругов из СТМ с введением опорных элементов в рабочий слой круга. В этом случае основное направление работ было ориентировано на то, что для обеспечения новых свойств рабочего слоя круга необходимо изменять не состав связующего, а применять стандартные, применительно к конкретным условиям обработки, связующие и, при этом, часть зерен СТМ заменять на так называемые „опорные элементы”, основной функцией которых и должно быть усиление самого слабого звена рабочей поверхности круга, а именно, связующего. Это фактически разработка абразивного инструмента с дискретным режущим слоем, в котором находятся режущие зерна и функциональные опорные твердые включения. В работе [1] нами приведены исследования, когда в рабочем слое круга чередуются режущие зерна и опорные элементы из сверхтвердых материалов функционального назначения. В работе [2] изложены исследования, когда в рабочий слой круга введены в качестве опорных элементов минеральные зернистые концентраты. Целью данной работы являлось исследование особенностей шероховатости обработанной поверхности при шлифова-