

: **1.** Porcelain enamel: the best protection for boilers and hot water tanks // Schmitz Apelt Italia Bulletin, 2003. – 8p. **2.** . . . . . : . . . . . / . . . . . , . . . . . : “ ”; : ( ), 2003.– 484 . **3.** Hans-Jürgen Thiele. Boiler Water Heater Inside Coating with Wet Enamel // Proc. of 20<sup>th</sup> Intern. enamellers Congr., Istanbul. 2005. – p.93–100. **4.** Il boiler, un elettrodomestico da valutare meglio // Smalto Porcellanato, 2002. – P.20-21.

666.293

\_\_\_\_\_ . . . . .

. . . . .

’ 5 500 -  
 : «Lorenzi Vasco», «Merloni  
 Termosanitari» ( ), «De Dietrich» ( ) .. « -  
 » « » ( ) « - » ( ).

— 2–3 — 1–2 [1]. 10 ,

( )

1987 . [4]

(PUESTA)

:

—

;

— 100% —  
 ;  
 — , —

[5,6].

PUESTA

[8].

1

1

|     | , .%             |                               |                                |                   |                   |                  |                               |     |     |      |      |     |                  |                  |                  |
|-----|------------------|-------------------------------|--------------------------------|-------------------|-------------------|------------------|-------------------------------|-----|-----|------|------|-----|------------------|------------------|------------------|
|     | SiO <sub>2</sub> | P <sub>2</sub> O <sub>5</sub> | Al <sub>2</sub> O <sub>3</sub> | Li <sub>2</sub> O | Na <sub>2</sub> O | K <sub>2</sub> O | B <sub>2</sub> O <sub>3</sub> | MgO | SrO | BaO  | CaO  | ZnO | TiO <sub>2</sub> | ZrO <sub>2</sub> | CaF <sub>2</sub> |
| [6] | 10               | 30-45                         | 20-40                          | 15-35             |                   |                  | 15                            | 15  |     |      |      |     | 10               |                  |                  |
| [7] | 68               |                               |                                | 2,5               | 15                |                  |                               |     |     |      |      |     | 3,23             | 4,95             | 6,32             |
| [8] | 43,65            |                               | 0,76                           | 8,1               | 13,65             | 2,59             | 11,0                          |     |     | 1,08 | 4,09 |     | 3,7              |                  | 5,68             |

2%.

$$v = 8 \cdot 10^7 - 10^8$$

80%,  
 4-5 ,  
 200°

**:1** Boni P. “Boiler in smalto porcellanato in Barca. Non soffrono il mal di mare”  
 garantisce ATI // Smalto Porcellanato, 1998. — 1. — 43–46. **2**  
 ( ) // . XV  
 , 1989. — .32. **3** Ainsworth J. Modern techniques for the application of  
 powder porcelain enamel // Vitreous Enameller. — 1995. — V.46, 1 — P.11–16. **4**  
 , 1990. — 576 . **5** J.Vernon. Black specking in  
 vitreous enamel powder applications// Vitreous enameller. — 1989. — 40, 3 — P. 52–55. **6** United  
 States Patent 7005396. Enamel composition. Espargillière S. (Saint Dizier, FR), Schanné A. (Hessheim,  
 DE), Roques F.(Viltry le François, FR). Filing Date:06/25/2001 Publication Date: 02/28/2006. **7** United  
 States Patent 4193808. Enamel for coating steel articles. Khodsky L. G. (Minsk, SU) Brazgovskaya A. I.  
 (Minsk, SU) Kaminskaya V. S. (Minsk, SU), Evgeny N..Filing Date:03/02/1977. Publication  
 Date:03/18/1980. **8** United States Patent 5075263. Enamel frits for acid-resistant one-coat enamelling on  
 unpickled steels. Schittenhelm H.-J. (Leverkusen, DE) Joseph W. (Cologne, DE). Filing Date:12/21/1990.  
 Publication Date:12/24/1991

621.357.7

