





1 – 59-1 ; – 770 ° :

( , )  
 ( , , , , )  
 ( ) ,  
 :  $t = t_r f_r + t_s f_s$  ( ) ,  
 ( ) :  
 $V = V_r f_r + V_s f_s$  , ( )  
 ( )  
 , -  
 ,  
 ( + ) - .  
 1) ,  
 59-1 ,  
 . 2) , 5 – 6  
 % ( )  
 ( 17 %), -  
 ( 10 %). 3)  
 1,8 4,7

1. Cahn, R. W. Physical metallurgy, 4th edition, 3-Volume Set, Volume 1, / R. W. Cahn, P Haasen // North Holland. – 1996. – 942 p.  
 2. Kadkhodapour, J. A micro mechanical study on failure initiation of dual phase steels under tension using single crystal plasticity model / J. Kadkhodapour, A. Butz, S. // Int. Journ. of Plasticity. – 2011. – Vol. 27 – P. 1103–1125.  
 3. Kuziak, R. Advanced high strength steels for automotive industry/ R. Kuziak, R. Kawalla, S. Waengler // Arch. of Civil and Mechan. Engineering. – 2008. – Vol. VIII, 2. – P. 102-117.  
 4. , . . , / . . , // , 2007. – 104, 3. – . 328-336.