AUTOMATED SILAR COATING SYSTEM DESIGN VIA MODULAR MICROCONTROLLER AND 3D PRINTING SOLUTIONS

Chornyi V.M., Dobrozhan A.I.
National Technical University
«Kharkiv Polytechnic Institute», Kharkiv

The SILAR (Successive Ionic Layer Adsorption and Reaction) coating technique is a cost-effective method for depositing thin nanostructured films, critical for photovoltaics, sensors, and catalysis applications. However, manual SILAR systems face reproducibility, scalability, and precise parameter control challenges. Integrating accessible technologies-microcontrollers (Arduino, ESP32, Raspberry Pi), 3D printing, and open-source software-offers a pathway to automate and optimize SILAR processes while retaining affordability and adaptability for research and small-scale industrial use.

A modular SILAR system could leverage Arduino or Raspberry Pi for real-time control of immersion cycles, temperature, and precursor solution pH. For instance, ESP32's wireless capabilities enable remote monitoring of deposition parameters, while stepper motors driven by microcontroller code ensure consistent substrate movement between solutions. 3D-printed components, such as customizable reactor vessels, substrate holders, or flow cells, reduce costs and enable rapid prototyping. Open-source CAD designs and affordable FDM/Resin 3D printers allow iterative hardware optimization – e.g., designing chemically resistant parts from PETG or PVDF filaments. Machine learning algorithms (deployable on Raspberry Pi 4) could refine deposition cycles by analyzing film quality data from integrated optical sensors or impedance spectroscopy modules.

Key advantages include scalability (from lab to pilot-scale systems), reproducibility via automated feedback loops, and adaptability to diverse materials (e.g., metal oxides, chalcogenides). Challenges remain in ensuring long-term chemical compatibility of 3D-printed parts and calibrating low-cost sensors for precise ionic concentration measurements. However, existing solutions, such as coating 3D-printed surfaces with inert polymers or using commercial pH/conductivity sensors, mitigate these limitations.

This approach democratizes advanced thin-film fabrication, enabling resource-limited labs to innovate in nanomaterials. By merging open-source hardware with SILAR's versatility, the system accelerates research and development cycles and bridges the gap between academic research and industrial production. Future work could explore AI-driven optimization of deposition parameters or hybrid systems combining SILAR with spin-coating/electrodeposition modules, further expanding its utility in next-generation material engineering.